


 *Laifual Drive*

Technical Requirements:

1. Please use the grease specified by our company (LF-2 or F-3).
2. The * in the drawing is the installation reference size, please follow the installation size requirements.
3. For details of size, please confirm with the delivery specification drawings.



LHT-32-XX-U-I

Model	Reduction ratio	Rated torque at 2000r/min input		Permissible peak torque at start and stop		Permissible maximum value for average load		Permissible maximum momentary torque		Permissible maximum input rotational speed (Grease)	Permissible average input rotational speed (Grease)	Backlash	weight	Desian life		
		Nm	kgfm	Nm	kgfm	Nm	kgfm	r/min	r/min							
Wave generator-A φ14	φ14H7	16.3 ^{+0.1}	5JS9/P9											10000		
Wave generator-A φ19	φ19H7	21.8 ^{+0.1}	6JS9/P9											15000		
Wave generator-A φ22	φ22H7	24.8 ^{+0.1}	6JS9/P9	50	76	7.8	216	22	108	11	382	39	4800	3500	≤20	LHT-I:2.54
		25.3 ^{+0.1}	8JS9/P9	80	118	12	304	31	167	17	568	58				
				100	137	14	333	34	216	22	647	66				
				120	137	14	353	36	216	22	686	70				