




LSN-25-XX-U-II



 *Laifual Drive*

| Model | Reduction ratio | Rated torque at 2000r/min input | | Permissible peak torque at start and stop | | Permissible maximum value for average load torque | | Permissible maximum momentary torque | | Permissible maximum input rotational speed(Grease) | Permissible average input rotational speed(Grease) | Backlash | Desian life |
|-------|-----------------|---------------------------------|------|---|------|---|------|--------------------------------------|------|--|--|----------|-------------|
| | | Nm | kgfm | Nm | kgfm | Nm | kgfm | Nm | kgfm | | | | |
| 25 | 50 | 39 | 4.0 | 98 | 10 | 55 | 5.6 | 186 | 19 | 5600 | 3500 | ≤20 | 10000 |
| | 80 | 63 | 6.4 | 137 | 14 | 87 | 8.9 | 255 | 26 | | | | 15000 |
| | 100 | 67 | 6.8 | 157 | 16 | 108 | 11 | 284 | 29 | | | | 15000 |
| | 120 | 67 | 6.8 | 167 | 17 | 108 | 11 | 304 | 31 | | | | 15000 |

Technical Requirements:

1. Please use the grease specified by our company (LF-2 or F-3).
2. The * in the drawing is the installation reference size, please follow the installation size requirements.
3. For details of size, please confirm with the delivery specification drawings.